

Nocken 55.01.03/042065

- 1) AF = Druckfeder aussen 66.01.04/043438
IF = Druckfeder innen 66.01.05/043439

Agraset 106

K 31			K 32			K 33			K 34			K 35			K 36		
M (Nm)	AF	IF	M (Nm)	AF	IF	M (Nm)	AF	IF	M (Nm)	AF	IF	M (Nm)	AF	IF	M (Nm)	AF	IF
100	4	-	220	9	-												
			260	10	-												
150	6	-	280	11	-												
160	6	-	300	12	-	450	18	-									
170	7	-							500	20	-						
180	7	-	330	13	-	500	20	-	550	22	-						
190	8	-							600	24	-						
200	8	-	360	14	-	550	22	-	650	26	-						
									700	28	-						
220	8	2	400	16	-	600	24	-									
									800	32	-						
240	8	3	450	16	4	650	24	4				1000	40	12			
									900	32	7						
260	8	4	500	16	7	700	24	7				1100	40	20			
									1000	32	22						
280	8	6	550	16	11	800	24	14				1200	40	28	1200	48	22
									1100	32	29	1300	40	36	1300	48	32
300	8	7	600	16	14	900	24	22							1400	48	42

- 1) Farbe schwarz *Noir*

Drehmoment-Toleranz $\pm 10 \%$



Paul Forrer AG 8048 Zürich
Aargauerstrasse 210
Hydr. deutsch: 044 439 19 91
Hydr. français: 044 439 19 92

KD-Normung

91.13.102

Nocken 55.01.03/042065

- 1) AF = Druckfeder aussen 66.01.26/043459
IF = Druckfeder innen 66.01.27/043460

Agraset 107

K 31			K 32			K 33			K 34			K 35			K 36		
M (Nm)	AF	IF	M (Nm)	AF	IF	M (Nm)	AF	IF	M (Nm)	AF	IF	M (Nm)	AF	IF	M (Nm)	AF	IF
						180	118	-									
			160	16	-	240	24	-									
			170	16	1												
			180	16	2	260	24	2									
			190	16	3												
40	4	-	200	16	4	280	24	4									
60	6	-	220	16	6	300	24	6	450	32	11						
80	8	-	240	16	8	330	24	9	500	32	16						
90	8	1															
100	8	2	260	16	10	360	24	12	550	32	21						
110	8	3															
120	8	4	280	16	11	400	24	15	600	32	26						
130	8	5										700	40	28	800	48	26
140	8	6	300	16	13	450	24	20	650	32	31	800	40	39	900	48	40
150	8	7															
160	8	8															

- 1) Farbe kupfer Kennzeichnung "X"

cuivre



paul forrer
Paul Forrer AG 8048 Zü-
Aargauerstrasse 250
Hydr. deutsch 044 439
Hydr. français 044 439