

## Schlauch-Übersicht für die GSP/GA-Armaturenreihe Aperçu de tuyaux pour raccord à sertir gamme GSP/GA

**Hydraulikschläuche** 1SN / 2SN / R4 – DN40–DN50  
**Tuyau hydraulique** 1SN / 2SN / R4 – DN40-DN50

Press-Hülsen  
nicht schälen!  
Douilles à sertir  
pas dénuder!

Press-Nippel  
nicht schälen!  
Raccord à sertir  
pas dénuder!



Nennweite Diamètre nominale			Norm Norme	Gates Schlauch / Tuyau	1)	p max. bar	Q max. l/min	GSP	GSP	2-tlg. Standardarmatur Raccord en 2 pcs.
mm	Zoll pouce	Code		Typ / Type				Bestell-Nr. N° de commande	Bestell-Nr. N° de commande	Bestell-Nr. N° de commande
40	1-½"	24	R4	<b>24GMV</b>	S	11	89	24GSP1F-2	24GSP	24GA
			1SN	<b>24G1</b>	R	50	272	24GSP1F-2	24GSP	24GA
			2SN	<b>24G2</b>	R	90	272	24GSP1F-2	24GSP	24GA
50	2"	32	R4	<b>32GMV</b>	S	8	158	32GSP1F-2	32GSP	32GA
			1SN	<b>32G1</b>	R	40	472	32GSP1F-2	32GSP	32GA
			2SN	<b>32G2</b>	R	80	472	32GSP1F-2	32GSP	32GA

1) empfohlen für: P = Druck-, R = Rücklauf-, S = Saug-, V = Vorsteuerleitung

1) recommande pour: P = pression, R = retour, S = aspiration, V = pilotage